

3M™ Cubitron™ II Bonded Abrasive  
Grinding and Cut-Off Wheels.

productivity  
solution company limited

CUBITRON™ II

**BORN TO  
GRIND.**

IT'S GRINDING REINVENTED.



FEATURING  
**NEW CUBITRON™ II**  
CUT & GRIND WHEELS

**3M**



# GRINDING REINVENTED



3M™ Cubitron™ II bonded abrasive grinding and cut-off wheels are revolutionizing the grinding process. They're faster cutting and longer lasting than conventional grinding wheels. With 3M precision-shaped grain technology that transforms the process of grinding metal, Cubitron II abrasives:

- Cut faster
- Stay sharp longer
- Require less pressure
- Potentially reduce operator fatigue
- Increase productivity



Conventional ceramic abrasive grain is irregular in shape. Instead of a clean, machining action, the grain "plows" through the metal, causing heat build up, slower cutting and shorter life.



3M precision-shaped grain in Cubitron II grinding wheels continuously fractures to form sharp points and edges – slicing cleaner and faster, staying cooler and lasting many times longer.

## 3 REASONS WHY IT'S BETTER:

1. *Cuts faster—helps improve productivity and throughput*
2. *Lasts longer—helps save money*
3. *Easier to use—good for your workers, good for your business*

## LESS PRESSURE REQUIRED, MORE MATERIAL REMOVED.

Competitive products require up to 3 times the amount of pressure to match the cut of Cubitron II abrasives.

## THE PAYOFF

- Less wear and tear on your operators
- More material removed by the same amount of effort
- Improved productivity

## USED IN INDUSTRIES SUCH AS:

Ship Building  
Structural Steel  
General Metal Fabrication  
Oil and Gas  
Agriculture  
Industrial and Construction Machinery




# 3M™ CUBITRON™ II CUT & GRIND WHEELS

**NEW**


Cubitron II Cut & Grind wheels are a versatile solution designed to use both as a depressed center grinding wheel and as a cut-off wheel—making them ideal for cutting, grinding, gouging and more. Optimized for use on mild and stainless steel.

## Cubitron II Cut & Grind Wheels Cut Faster!



After 10 min., nearly double the output of our closest competitor

## Cubitron II Cut & Grind Wheels Last Longer!



Removes nearly 2x the material, compared to our closest competitor

## 3M™ CUBITRON™ II CUT & GRIND WHEEL – T27

### Performance Characteristics

- 3M precision-shaped grain for ultra fast cut and long life
- Versatile—use as both a grinding wheel *and* cut-off wheel
- Specially formulated for use on stainless and mild steel
- Cool cutting for a higher quality and faster cut

### D x T x AH

### UPC

### Max. RPM

### Inner/Case

4" x 1/8" x 3/8"	4046719-82276-8	15,300	10/20
4" x 1/8" x 5/8"	4046719-82277-5	15,300	10/20
4.5" x 1/8" x 7/8"	4046719-82279-9	13,300	10/20
5" x 1/8" x 7/8"	4046719-82278-2	12,250	10/20
6" x 1/8" x 7/8"	051141-28758-4	10,200	10/20
7" x 1/8" x 7/8"	051141-28760-7	8,500	10/20
9" x 1/8" x 7/8"	051141-28761-4	6,650	10/20

## 3M™ CUBITRON™ II CUT & GRIND WHEEL – T27 QUICK CHANGE HUB

### Performance Characteristics

- 3M precision-shaped grain for ultra fast cut and long life
- Versatile—use as both a grinding wheel *and* cut-off wheel
- Specially formulated for use on stainless and mild steel
- Cool cutting for a higher quality and faster cut
- Quick change attachment for improved productivity and throughput

### D x T x AH

### UPC

### Max. RPM

### Inner/Case


4.5" x 1/8" x 5/8-11"	051141-28762-1	13,300	10/20
5" x 1/8" x 5/8-11"	051141-28763-8	12,250	10/20
6" x 1/8" x 5/8-11"	051141-28764-5	10,200	10/20
7" x 1/8" x 5/8-11"	051141-28765-2	8,500	10/20
9" x 1/8" x 5/8-11"	051141-28766-9	6,650	10/20



# 3M™ CUBITRON™ II DEPRESSED CENTER GRINDING WHEELS



Cubitron II depressed center grinding wheels produce very high cut rates on a wide variety of metals. They are used for heavy weld removal and many other grinding applications.



As the chart shows, after ten minutes of grinding, Cubitron II grinding wheels **tripled the output** of its competitors.

## 3M™ CUBITRON™ II DEPRESSED CENTER GRINDING WHEEL T27

### Performance Characteristics

- Premium Performance
- 3M precision-shaped grain for ultra fast cut and long life
- Specially formulated for use on stainless and mild steel
- Cool cutting for a higher quality and faster cut
- Fast, cool cutting helps extend the life of the tool

D x T x AH	UPC	Max. RPM	Inner/Case
4" x 1/4" x 3/8"	051115-66598-1	15,300	10/20
4" x 1/4" x 5/8"	051115-66597-4	15,300	10/20
4.5" x 1/4" x 7/8"	051115-66587-5	13,300	10/20
5" x 1/4" x 7/8"	051115-66588-2	12,250	10/20
6" x 1/4" x 7/8"	051115-66589-9	10,200	10/20
7" x 1/4" x 7/8"	051115-66590-5	8,500	10/20
9" x 1/4" x 7/8"	051115-66591-2	6,650	10/20

## 3M™ CUBITRON™ II DEPRESSED CENTER GRINDING WHEEL T27 QUICK CHANGE

### Performance Characteristics

- Premium Performance
- 3M precision-shaped grain for ultra fast cut and long life
- Specially formulated for use on stainless and mild steel
- Cool cutting for a higher quality and faster cut
- Fast, cool cutting helps extend the life of the tool
- Quick change attachment for improved productivity and throughput

D x T x AH	UPC	Max. RPM	Inner/Case
4.5" x 1/4" x 5/8-11"	051115-66596-7	13,300	10/20
5" x 1/4" x 5/8-11"	051115-66592-9	12,250	10/20
6" x 1/4" x 5/8-11"	051115-66593-6	10,200	10/20
7" x 1/4" x 5/8-11"	051115-66594-3	8,500	10/20
9" x 1/4" x 5/8-11"	051115-66595-0	6,650	10/20




# 3M™ CUBITRON™ II CUT-OFF WHEELS



Cubitron II cut-off wheels are designed to provide high cut rates and long life on all types of ferrous metals, stainless steels, alloy steels and cast iron.

*Cubitron II cut-off wheels have over 2 times the life of competitive wheels and cut faster too, translating to lower costs.*



## 3M™ CUBITRON™ II CUT-OFF WHEEL T1

### Performance Characteristics

- Premium performance
- 3M precision-shaped grain for ultra fast cool cutting action and long life
- Specially formulated for use on stainless and mild steel
- Cool cutting for a higher quality and faster cut
- Fast, cool, cutting helps extend the life of the tool

D x T x AH	UPC	Max. RPM	Inner/Case
3" x .035" x 1/4"	051115-66513-4	25,465	25/50
3" x .035" x 3/8"	051115-66514-1	25,465	25/50
3" x .06" x 3/8"	051115-66516-5	25,465	25/50
4" x .035" x 3/8"	051115-66518-9	19,100	25/50
4" x .06" x 3/8"	051115-66520-2	19,100	25/50
4" x .045" x 5/8"	051115-66522-6	15,300	25/50
4" x .125" x 3/8"	051115-66524-0	19,100	25/50
4.5" x .045" x 7/8"	051115-66525-7	13,300	25/50
5" x .045" x 7/8"	051115-66526-4	12,250	25/50
6" x .045" x 7/8"	051115-66527-1	10,200	25/50
7" x .045" x 7/8"	051115-66528-8	8,500	25/50

## 3M™ CUBITRON™ II CUT-OFF WHEEL T27

### Performance Characteristics

- Premium performance
- 3M precision-shaped grain for ultra fast cool cutting action and long life
- Specially formulated for use on stainless and mild steel
- Cool cutting for a higher quality and faster cut
- Fast, cool, cutting helps extend the life of the tool

D x T x AH	UPC	Max. RPM	Inner/Case
4.5" x .045" x 7/8"	051115-66531-8	13,300	25/50
5" x .045" x 7/8"	051115-66537-0	12,250	25/50
5" x .09" x 7/8"	051115-66539-4	12,250	25/50
6" x .045" x 7/8"	051115-66541-7	10,200	25/50

## 3M™ CUBITRON™ II CUT-OFF WHEEL T27 QUICK CHANGE

### Performance Characteristics

- Premium performance
- 3M precision-shaped grain for ultra fast cool cutting action and long life
- Specially formulated for use on stainless and mild steel
- Cool cutting for a higher quality and faster cut
- Fast, cool, cutting helps extend the life of the tool

D x T x AH	UPC	Max. RPM	Inner/Case
4.5" x .045" x 5/8-11"	051115-66530-1	13,300	25/50
4.5" x .125" x 5/8-11"	051115-66534-9	13,300	25/50
6" x .045" x 5/8-11"	051115-66540-0	10,200	25/50


- Quick change attachment for improved productivity and throughput



# 3M™ HIGH PERFORMANCE DEPRESSED CENTER GRINDING WHEELS



For the ideal combination of value and performance, choose these 3M High Performance depressed center grinding wheels. They feature 3M ceramic abrasive grain for fast cut and long life, and are specially formulated for use on stainless and mild steel.



## 3M™ HIGH PERFORMANCE DEPRESSED CENTER GRINDING WHEEL T27

### Performance Characteristics

- 3M ceramic abrasive grain provides fast cut and long life
- Specially formulated for use on stainless and mild steel

D x T x AH	UPC	Max. RPM	Inner/Case
4" x 1/4" x 3/8"	051115-66555-4	15,300	10/20
4" x 1/4" x 5/8"	051115-66554-7	15,300	10/20
4.5" x 1/4" x 7/8"	051115-66544-8	13,300	10/20
5" x 1/4" x 7/8"	051115-66545-5	12,250	10/20
6" x 1/4" x 7/8"	051115-66546-2	10,200	10/20
7" x 1/4" x 7/8"	051115-66547-9	8,500	10/20
9" x 1/4" x 7/8"	051115-66548-6	6,650	10/20

## 3M™ HIGH PERFORMANCE DEPRESSED CENTER GRINDING WHEEL 27 QUICK CHANGE

### Performance Characteristics

- 3M ceramic abrasive grain provides fast cut and long life
- Specially formulated for use on stainless and mild steel
- Quick change attachment for improved productivity and throughput

D x T x AH	UPC	Max. RPM	Inner/Case
4.5" x 1/4" x 5/8-11"	051115-66553-0	13,300	10/20
5" x 1/4" x 5/8-11"	051115-66549-3	12,250	10/20
6" x 1/4" x 5/8-11"	051115-66550-9	10,200	10/20
7" x 1/4" x 5/8-11"	051115-66551-6	8,500	10/20
9" x 1/4" x 5/8-11"	051115-66552-3	6,650	10/20



# 3M™ HIGH PERFORMANCE CUT-OFF WHEELS

For the ideal combination of value and performance, choose these 3M High Performance cut-off wheels for the job. They feature 3M ceramic abrasive grain for fast cut and long life, and are specially formulated to be used on stainless and mild steel.



## 3M™ HIGH PERFORMANCE CUT-OFF WHEEL T1

### Performance Characteristics

- Specially formulated for use on stainless and mild steel

D x T x AH	UPC	Max. RPM	Inner/Case
3" x .035" x 3/8"	051115-66557-8	25,465	25/50
3" x .06" x 1/4"	051115-66558-5	25,465	25/50
3" x .06" x 3/8"	051115-66559-2	25,465	25/50
4" x .035" x 3/8"	051115-66561-5	19,100	25/50
4" x .035" x 5/8"	051115-66562-2	15,300	25/50
4" x .06" x 3/8"	051115-66563-9	19,100	25/50
4" x .09" x 5/8"	051115-66564-6	15,300	25/50
4" x .045" x 5/8"	051115-66565-3	15,300	25/50
4" x .125" x 3/8"	051115-66567-7	19,100	25/50
4.5" x .045" x 7/8"	051115-66568-4	13,300	25/50
5" x .045" x 7/8"	051115-66569-1	12,250	25/50
6" x .045" x 7/8"	051115-66570-7	10,200	25/50
7" x .045" x 7/8"	051115-66571-4	8,500	25/50

## 3M™ HIGH PERFORMANCE CUT-OFF WHEEL T27

### Performance Characteristics

- Specially formulated for use on stainless and mild steel

D x T x AH	UPC	Max. RPM	Inner/Case
4.5" x .045" x 7/8"	051115-66574-5	13,300	25/50
4.5" x .125" x 7/8"	051115-66578-3	13,300	25/50
5" x .045" x 7/8"	051115-66580-6	12,250	25/50
5" x .09" x 7/8"	051115-66582-0	12,250	25/50
6" x .045" x 7/8"	051115-66584-4	10,200	25/50

## 3M™ HIGH PERFORMANCE CUT-OFF WHEEL T27 QUICK CHANGE

### Performance Characteristics

- 3M ceramic abrasive grain provides fast cut and long life
- Quick change attachment for improved productivity and throughput

D x T x AH	UPC	Max. RPM	Inner/Case
4.5" x .045" x 5/8-11"	051115-66573-8	13,300	25/50
4.5" x .125" x 5/8-11"	051115-66577-6	13,300	25/50
6" x .045" x 5/8-11"	051115-66583-7	10,200	25/50





**FOR MORE INFORMATION VISIT [3M.COM/ABRASIVES](http://3M.COM/ABRASIVES)**

**PRODUCT USE:** All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

**WARRANTY AND LIMITED REMEDY:** 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product packaging, package inserts, price pages, or 3M product literature. **3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is proved defective, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to repair or replace the product or refund the purchase price.

**LIMITATION OF LIABILITY:** Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

### **Productivity Solution Co., Ltd**

59 Flourish Buidling, 7<sup>th</sup> floor , Soi Ratchadapisek 18,  
Ratchadapisek Rd., Huaykwang  
Huaykwang, Bangkok 10310  
Tel: +662-119 1955 -6  
Fax: +662-119 1959  
Mobile: +6682-7880208